



ECO 16

COD Thermoreactor

16-position thermoreactor for Chemical Oxygen Demand (COD)
with settable temperature and operating time



Precise, Intuitive and Versatile

COD Analysis Thermoreactor ECO 16 ensures a simple and easy programming of time and temperature, the parameters involved in the analysis.

- Electronic temperature control
- Temperature regulation from ambient to 165 °C
- Analysis time can be set from 1 to 999 minutes or continuous
- Processes up to 14 x Ø 16 mm test tubes
- Plus 2 x Ø 22 mm test tubes simultaneously
- LCD countdown display shows the temperature and remaining time
- COD analysis in only 30 minutes at 160 °C



INSTRUMENT - CODE

ECO 16	230 V / 50-60 Hz	F10100126
ECO 16	115 V / 50-60 Hz	F10110126

TECHNICAL DATA

CONSTRUCTION MATERIAL	Epoxy painted metal structure
HOLES NUMBER AND DIAMETER	14 pos. (Ø 16 mm) and 2 pos. (Ø 22 mm)
SET TEMPERATURE	Display visualization
COUNTDOWN	Display visualization
SELECTABLE WORKING TEMPERATURES	From room temperature to 165 °C, resolution 1 °C
SELECTABLE WORKING TIMES	From 0 to 999 minutes or continuous operation
TEMPERATURE STABILITY	± 0.5 °C
TEMPERATURE HOMOGENEITY	± 0.5 °C
TEMPERATURE PRECISION	± 1 °C
VISUAL SIGNAL	Reaching of set temperature, Countdown
ACOUSTIC AND VISUAL SIGNAL	End of cycle, Probe interruption, Broken probe, Exceed temperature range
DIMENSION (WXHXD)	168x110x269 mm (6.4x4.3x10.6 in)
POWER	550 W
WEIGHT	3,8 Kg (8.4 lb)



We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

DESIGNED AND MANUFACTURED IN ITALY



ITALY - HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
40, Burt Drive, Unit #1, Deer Park
NY 11729 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

LATAM
velplatam@velp.com

CHINA
Xinlong Rd Building 28, Lane 1333
Shanghai city - China
Tel. +8621 34500630
velpchina@velp.com