



CSF6

Dietary fiber analyzers

Filtration unit for dietary fiber extraction



Rapid and efficient filtration

CSF6 is the robust Filtration unit for the final filtration and washing phase defined in the enzymatic method for dietary fiber extraction.

- CFS6 filtration unit is able to perform single or multiple samples at the same time, up to a maximum of 6 samples at the same time
- The high efficient pump allows to speed-up the filtration step and the final washing.
- Single or multiple sample processing
- Short filtration time – under 20 minutes, even for 6 samples
- Electronic setting of counter pressure



INSTRUMENT - CODE

CSF6	230 V / 50 Hz	F30420210
CSF6	230 V / 60 Hz	F30430210
CSF6	115 V / 60 Hz	F30440210

TECHNICAL DATA

CONSTRUCTION MATERIAL	Epoxy painted stainless steel structure
COUNTERPRESSURE	Electronic setting
RESIDUES COLLECTING	Separate
FILTRATION	Peristaltic pump with high suction capacity
POWER	220 W
WEIGHT	28 Kg (61.6 lb)
DIMENSIONS (WXHXD)	750x420x380 mm (28.7x16.5x15 in)



We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

DESIGNED AND MANUFACTURED IN ITALY



ITALY – HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
155 Keyland Court, Bohemia
NY 11716 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

CHINA
Xinlong Rd Building 28, Lane 1333
Shanghai city - China
Tel. +86 18017557329
velpchina@velp.com